








































| Image | Item Number | Item Description | Price (Excl. GST) | Technical information |
|-------|-------------|--|-------------------|--|
| | 2034358 | Cordless rotary hammer TE 2-A22 case | \$ 240.00 | Weight: 2.7Kg Optimum Drilling Range: 4 - 12mm |
| | 2034359 | Cordless rotary hammer TE 2-A22 box | \$ 200.00 | Application: Light duty Drilling and hammer drilling in concrete and masonry Weight: 2.7Kg Optimum Drilling Range: 4 - 12mm |
| | 2098481 | Cordless rotary hammer TE 4-A22 box | \$ 260.00 | Application: Drilling and hammer drilling in concrete and masonry Weight: 3.3Kg Optimum Drilling Range: 5 - 12mm |
| | 2098475 | Cordless rotary hammer TE 4-A22 case | \$ 280.00 | Application: Drilling and hammer drilling in concrete and masonry Weight: 3.3Kg Optimum Drilling Range: 5 - 12mm |
| | 2098484 | Dust removal system TE DRS-4-A case | \$ 130.00 | Application: On-board vacuum system for dust collection, for use with TE 4-A22 Gen 2 Hammer Drilling Range: 4 - 16mm Max drilling depth: 100mm |
| | 2162758 | Cordless rotary hammer TE 6-A22 case | \$ 380.00 | Application: Drilling and hammer drilling in concrete and masonry + Light chiselling Weight: 3.7Kg Optimum Drilling Range: 6 - 16mm |
| | 2162794 | Cordl. Dispenser HDE 500-A22 box (Chem anchor dispenser) | \$ 200.00 | Application: Injecting Hilti HIT epoxy or adhesive mortar for fastening anchor rods and rebar in concrete and masonry |
| | 2184337 | Cordl. ham. dr. driver SF 6H-A22 case | \$ 310.00 | Application: Masonry + Wood Drilling, self driving screws No Load RPM: Gear 1: 490 rpm; gear 2: 2000 rpm Max Torque (soft/hard joint): 65 Nm (soft joint), 80 Nm (hard joint) |
| | 2061305 | Cordl. drill driver SF 8M-A22 case | \$ 300.00 | Application: Drilling in Metal with HSS bits up to 20 mm diameter No Load RPM: Gear 1: 320 rpm; gear 2: 550 rpm; gear 3: 1250 rpm; gear 4: 2150 rpm Max Torque (soft/hard joint): 50 Nm (soft joint), 84 Nm (hard joint) |
| | 2186918 | Cordl. area light SL 6-A22 box | \$ 160.00 | Application: Illumination of unlit and poorly lit work areas Brightness: 3000 lm Weight: 3.19Kg |
| | 2187660 | Vacuum cleaner VC 5-A22 | \$ 223.09 | Application: Compact and cordless construction vacuum for jobsite clean ups (dry) Tank Size / Dust capacity: 3.5L / 3Kg Max Suction: 11.5 kPa |
| | 2005040 | Cordl. circular saw SCM 22-A box | \$ 280.00 | Application: Cutting channel, pipe, sheet metal, mesh & sandwich panels Max cutting depth: 57mm Blade Diameter: 165mm |
| | 2005019 | Cordl. circular saw SCM 22-A case | \$ 310.00 | Application: Cutting channel, pipe, sheet metal, mesh & sandwich panels Max cutting depth: 57mm Blade Diameter: 165mm |
| | 2206610 | Cordl. angle grinder AG 4S-A22-125 case | \$ 210.00 | Application: Cutting, grinding & polishing Disc Diameter.: 125mm |
| | 2109985 | Cordl. angle grinder AG 125-A22 case | \$ 250.00 | Application: Cutting, grinding & polishing - Dead-man switch Disc Diameter.: 125mm Weight: 2.7Kg |
| | 2101170 | Cordl. angle grinder AG 125-A36 case | \$ 260.00 | Application: 36v - Cutting, grinding & polishing - Paddle with Dead-man switch Disc Diameter.: 125mm Weight: 3.45Kg |
| | 2101177 | Cordl. angle grinder AG 150-A36 case | \$ 280.00 | Application: 36v - Cutting, grinding & polishing - Paddle with Dead-man switch Disc Diameter.: 150mm Weight: 3.45Kg |
| | 2119153 | Angle grinder AG 125-19SE | \$ 549.00 | Application: Corded 1900W, Cutting, grinding & polishing Disc Diameter.: 125mm Weight: 2.5Kg |
| | 3667384 | AG 125 19SE - 3 Pack Combo | \$ 1,499.00 | Application: Corded 1900W, Cutting, grinding & polishing Disc Diameter.: 125mm Weight: 2.5Kg |
| | 2119160 | Angle grinder AG 125-15DB | \$ 600.00 | Application: Corded 1500W, Cutting, grinding & polishing - Dead-man switch Disc Diameter.: 125mm Weight: 2.7Kg |
| | 2162154 | Cordl. reciprocating saw SR 30-A36 case | \$ 380.00 | Application: 36v - Heavy duty demolition and cutting to length Stroke Length.: 32mm Weight: 3.3Kg |
| | 2161956 | Cordl. reciprocating saw SR 6-A22 case | \$ 320.00 | Application: Heavy duty demolition and cutting to length Stroke Length.: 32mm Weight: 3.8Kg |

| | | | | |
|--|---------|--|-------------|--|
|  | 2133678 | Cordl. orbital jig saw SJT 6-A22 case | \$ 280.00 | Application. T Grip - Cutting wood, metal & sandwich panel Stroke Length.: 28mm Max Bevel Angle: 45 ° |
|  | 2133670 | Cordl. orbital jig saw SJD 6-A22 box | \$ 240.00 | Application. D Handle - Cutting wood, metal & sandwich panel Stroke Length.: 28mm Max Bevel Angle: 45 ° |
|  | 2133673 | Cordl. orbital jig saw SJD 6-A22 case | \$ 280.00 | Application. D Handle - Cutting wood, metal & sandwich panel Stroke Length.: 28mm Max Bevel Angle: 45 ° |
|  | 2133056 | Extraction adapter SJ | \$ 3.00 | Dust removal system and components for sawing with Hilti jig saws |
|  | 2218557 | Cordl. riveting tool RT 6-A22 case | \$ 570.00 | Application. Fastening rivets in Aluminium, Stainless steel, Steel Rivet Range diameter: 2.4 - 5 mm Weight: 1.65Kg |
|  | 2243817 | Slitting shear SSH 6-A22 box | \$ 500.00 | Application. fast, straight or curved cuts in sheet metal, spiral ductwork and other everyday metal fabrication up to 2.5 mm (12 Gauge) thickness Weight: 2.2Kg |
|  | 2149568 | Band saw SB 4-A22 box | \$ 180.00 | Application. Cutting Metal, Stainless steel Cutting Depth: 63.5mm Weight: 3.15kg |
|  | 2193410 | Cordl. cut-out tool SCO 6-A22 box | \$ 230.00 | Application. All basic plasterboard cut-outs No Load Gear: gear 1: 30000 rpm Weight: 1.4Kg |
|  | 423166 | Cordl. circular saw SCW 22-A box | \$ 240.00 | Application. Cutting wood, sandwich panel up to 57mm depth + upto 50 ° bevel Blade Diameter: 165mm Weight: 4.1Kg |
|  | 423165 | Cordl. circular saw SCW 22-A case | \$ 280.00 | Application. Cutting wood, sandwich panel up to 57mm depth + upto 50 ° bevel Blade Diameter: 165mm Weight: 4.1Kg |
|  | 2089089 | Cordl. circular saw SC 70W-A22 box | \$ 270.00 | Application. Cutting wood, sandwich panel up to 70mm depth + upto 50 ° bevel Blade Diameter: 190mm Weight: 4.8Kg |
|  | 2089210 | Cordl. circular saw SC 70W-A22 case | \$ 310.00 | Application. Cutting wood, sandwich panel up to 70mm depth + upto 50 ° bevel Blade Diameter: 190mm Weight: 4.8Kg |
|  | 2093434 | Cordl. impact driver SID 8-A22 case | \$ 370.00 | Application. impact driver with 7/16" hexagonal chuck for heavy-duty timber work Max Torque: 550 Nm Weight: 2.6Kg |
|  | 2242016 | Cordl. imp. wrench SIW 9-A22 3/4" case | \$ 420.00 | Application. high-torque impact wrench with 3/4" through hole anvil Max Torque: 800 Nm Weight: 2.86Kg |
|  | 409459 | Cordl. imp. wrench SIW 22T-A 1/2" case | \$ 300.00 | Application. high-torque cordless impact wrench with 1/2" detent pin anvil Max Torque: 450 Nm Weight: 2.17Kg |
|  | 2138585 | Adaptive torque module SI-AT-A22 | \$ 390.00 | Application. Torque module control to be used with SIW 6AT-A22 for anchoring and bolting in line with approvals Weight: 0.26Kg |
|  | 2256540 | Tool case SF + SI 2 empty | \$ 80.00 | Hard-sided case for storing and transporting multiple tools with their accessories |
|  | 2243477 | Cordless breaker TE 500-A36 | \$ 1,050.00 | Application. 36v - SDS Max breaker for chiselling in concrete and masonry Single Impact Energy: 7.8j |
|  | 2183172 | Battery pack B 36/9.0 Li-ion | \$ 390.00 | Ultimate-power 36V 9.0 Ah Li-ion battery for extreme run time Weight: 2.03Kg |
|  | 2098208 | Battery pack B 36/2.6 | \$ 130.00 | Ultimate-power 36V 2.6 Ah Li-ion battery for extreme run time |
|  | 2119234 | DC car charger C 4/36-DC box | \$ 110.00 | Multi-voltage DC car charger for all Gen 1 22v + 36v Hilti Li-ion batteries |
|  | 2108817 | Multi-bay charger C 4/36-MC4 240V box | \$ 200.00 | Multi-voltage, multi-bay charger for all Gen 1 22v + 36v Hilti Li-ion batterie |
|  | 2312354 | Floor scraper TE-CX FS | \$ 120.00 | Extra-sharp SDS Plus (TE-C) floor scraper chisels for removing flooring and coatings Width: 100mm |

| | | | | |
|--|---------|-------------------------------|-----------|---|
|  | 2312355 | Floor scraper TE-YX FS | \$ 264.00 | SDS Max (TE-Y) floor scraper chisels for removing flooring and coatings Width: 150mm Length: 630mm |
|  | 2312356 | Floor scraper TE-SX FS | \$ 288.00 | TE-S floor scraper chisels for removing flooring and coatings using demolition tools Width: 152mm |
|  | 2312359 | Joint chisel TE-CX JO 25 | \$ 100.00 | SDS Plus (TE-C) joint chisels for removing mortar Width: 32mm |
|  | 2207027 | Tile chisel TE-YX TI 50/12 | \$ 88.00 | Self-sharpening SDS Max (TE-Y) tile chisels for scraping away surface materials Length: 500mm Width: 120mm |
|  | 2254656 | Tile chisel TE-SX TI 50/12 | \$ 116.00 | Self-sharpening TE-S tile chisels for scraping away surface materials Length: 500mm Width: 120mm |
|  | 406785 | Clay spade TE-SX SP 50 | \$ 128.00 | Extra-sharp TE-S clay spade chisels for breaking up hard-packed gravel or dirt Length: 500mm Width: 115mm |
|  | 2254759 | Clay spade TE-HX SP 50 | \$ 160.00 | Clay spade chisel bit for digging and loosening terrain using third-gen TE 3000 or H28 demolition tools with clamp Length: 500mm |
|  | 2207028 | Bushing tool TE-YX BT 4x4 | \$ 120.00 | SDS Max (TE-Y) bushing tool for surface work and layer removal in concrete Length: 250mm Bushing head dimensions (L x W): 40 mm x 40mm |
|  | 1829 | Bushing head TE-Y/S BH 4x4 | \$ 148.00 | Universal bushing tool head for surface roughening using SDS Max (TE-Y) + TE-S shanks Length: 50mm Bushing head dimensions (L x W): 40 mm x 40mm |
|  | 2312436 | Tamper plate TE-Y/S TP 15x15 | \$ 172.00 | Ultra-robust tamping plate for compacting earth and gravel using SDS Max (TE-Y) or TE-S shanks |
|  | 2312432 | Shank TE-Y SH 30 | \$ 33.60 | Ultra-robust SDS Max (TE-Y) shanks for connecting tamping plates and bushing heads to a compatible breaker Length: 300mm |
|  | 406786 | Shank TE-S SH 45 | \$ 64.00 | Ultra-robust TE-S shanks for connecting tamping plates and bushing heads to a compatible breaker Length: 450mm |
|  | 2254761 | Shank TE-H SH 40 | \$ 120.00 | Ultra-robust shanks for connecting tamping plates and bushing heads to a compatible breaker using the third-gen TE 3000 or H28 demolition tools with clamp Length: 400mm |
|  | 2312433 | Shank TE-H17 SH 28 | \$ 48.00 | Ultra-robust Hex 28 shanks for connecting tamping plates and bushing heads to a compatible breaker Length: 400mm |
|  | 436072 | Rod driver head TE-Y/S RH 2 | \$ 41.60 | Universal earth rod setter head for use with the SDS Max (TE-Y) and TE-S shank Inner Diameter: 20mm |
|  | 436073 | Rod driver head TE-Y/S RH 2.5 | \$ 43.20 | Universal earth rod setter head for use with the SDS Max (TE-Y) and TE-S shank Inner Diameter: 25mm |
| <p>*All clearance products are offered subject to stock availability at the time of purchase. Prices and availability may change without notice. Clearance products are not eligible for fleet management. To the fullest extent permitted by law, Hilti (Aust.) Pty. Ltd. makes no warranties, express or implied, regarding the availability, suitability, or fitness for purpose of clearance products.</p> | | | | |