



Inspection Documents  
 EN 10204  
 Prüfbescheinigungen

HILTI (CHINA) LTD.  
 Yongping Road, South,  
 Zhanjiang, Guangdong, PRC  
 Tel : (86) 759 3379226

Inspection Document / Prüfbescheinigung  
检验文件

**HILTI MO: Hilti (Aust.) Pty Ltd**  
**Address: 1 Homebush Bay Drive, Bldg. G**  
**City: Rhodes N.S.W.**  
**State:**  
**Zip code: 2138**  
**Fax No :**

Document  
 Dokument No: 115/2016  
 文件号

**Inspection Document/ Prüfbescheinigung**  
 Certificate of compliance - Werksbescheinigung 2.1   
 Test Report - Werkszeugnis 2.2   
 Specific Test Report - Abnahmeprüfzeugnis 3.1

Item No. Artikel-Nr. 工件号	Product Designation Produktbezeichnung 工件名称	Order No. Auftrags-Nr. 订单号	Batch No. Charge / Los-Nr. 批号	Quantity Menge 数量
2121863	Anchor rod HIT-C-F-8.8 M24x450	N/A	N/A	N/A


Remarks:  
 Bemerkungen:  
 备注 :

We herewith certify, that the material described above complies with the terms of the order.  
 Hiermit bestätigen wir, dass die oben angeführte Lieferung den Vereinbarungen bei der Bestellung entspricht.  
 特此证明, 以上所示的工件符合合同的要求。

Postal Information

Name:  
 Address:  
 Tel /Fax No.:

Responsible Department  
 Verantwortliche Stelle  
 Service responsible  
 Date 5-Apr-16  
 Datum  
 日期

  
**Signature / Visum / 签名**  
 for HILTI (CHINA) LTD



**Inspection Documents**  
**EN 10204**  
**Prüfbescheinigungen**

HILTI (CHINA) LTD.  
Yongping Road, South,  
Zhanjiang, Guangdong, PRC  
Tel : (86) 759 3379226

**Results of the inspections / Ergebnisse der Prüfungen / 检查结果**

Blatt "A"

Document No Dokument Nr. 文件号: 115/2016	Pos. 1	Pos. 2	Pos. 3	Pos. 4	Pos. 5	Pos. 6
Item designation Artikelbezeichnung 零部件名称	Rod 螺杆	Nut 螺母	Washer 垫片			
Item No. Artikel Nr. 工件号	2121861	15720	352157			
Material Werkstoff 材料	8.8	8	HV140			
Standard Norm 标准	ISO 898-1	DIN 934	DIN 125-1			
Batch No. Charge / Los-Nr. 批号						
Receipt No Eingangs-Nr 收料号	711370 711124	707639 706656	705279			

**Inspections / Prüfungen / 检查**

Chemical Composit. Chem.Zusammensetzung 化学成分	POS. 1	POS. 2	POS. 3	POS. 4	POS. 5	POS. 6
C %	0.41	0.35				
Si %						
Mn %		0.75				
P %	0.015	0.015				
S %	0.009	0.011				
Cr%						
Ni%						
Mo%						
N%						
Mech. Properties Mech. Eigenschaften 机械性能	POS. 1	POS. 2	POS. 3	POS. 4	POS. 5	POS. 6
Rm (N/mm2)	885-978					
Rp (N/mm2)	756-880					
A5 %	15-17					
HV			163-179			
HRC *						
Fp		282				
Z %						
Zinc Coating Thickness Zinkschichtdicke 镀锌层厚度	POS. 1	POS. 2	POS. 3	POS. 4	POS. 5	POS. 6
Zn(µm)	45-97	40-75	42-71			

Rm	N/mm2	Ultimate tensile strength 最大抗拉强度	Zn	µm	Zinc Coating Thickness 镀锌层厚度
Rp0.2	N/mm2	Yield Strength 屈服强度	HV		Vickers hardness 维氏硬度
A5	%	Elongation after fracture 延伸率(断裂后)	Fp	KN	Proof load 保证载荷

\* : Tested by P8