

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** Hilti OneStep Anchor HOS-C N30

· **Container size** HOS-C 120 - 250

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU2a Mining, (without offshore industries)

· **Application of the substance / the preparation**

Rock anchor for the stabilization of tunnels, galleries and the like in mining.

The Hilti OneStep-Anchor is classified as an article in accordance with section 3, paragraph 5, of the EC Chemicals Bill. The product is not subject to identification regulations under EC Directives and the Ordinance on Hazardous Materials.

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
Rhodes N.S.W. 2138
Australia
Phone: 131 292
Fax: 1300 135 042
Email: serviceaustralia@hilti.com

· **Informing department:**

anchor.hse@hilti.com
see section 16

· **Emergency telephone number:**

Schweizerisches Toxikologisches Informationszentrum - 24 h Service
Tel.: 0041 / 44 251 51 51 (international)

Hilti (Aust.) Pty. Ltd.
Phone: 131 292
Fax: 1300 135 042

2 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

In accordance with article 3 (3) of REACH, this / these item(s) are products.

A product is not subject to the mandatory marking regulations applicable to dangerous substances.

The product is not classified as hazardous to health or environment according to the CLP regulation.

· **Additional information:**

The OneStep-Anchor presents no hazards to be particularly mentioned if used correctly.
Please note the information of this Material Safety Data Sheet.

The OneStep-Anchor forms a unit in which the constituents are contained in encapsulated form (dual foil pack) inside a steel tube. Access to the integrated foil pack and thus to the components A and B is possible only through intentional, forceful manipulation and misuse of the product.

The integrated dual foil pack contains inflammable constituents.

The inhalation of styrene vapors is harmful.

Skin contact with component B (white) may cause sensitization.

Components A and B are irritating to the eyes and skin.

Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed

The usual measures for work hygiene and the governmental regulations must be followed

· **Label elements**

· **Labelling according to Regulation (EC) No 1272/2008** Void

· **Hazard pictograms** Void

· **Signal word** Void

· **Hazard statements** Void

· **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P235+P410 Keep cool. Protect from sunlight.

(Contd. on page 2)

Trade name: Hilti OneStep Anchor HOS-C N30

(Contd. of page 1)

- P261 Avoid breathing vapours.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.

· Additional information:

Safety data sheet available on request.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description:

Rock anchor with internally integrated 2-component foil pack.

The foil pack unit contains:

Unsaturated polyester resin with styrene, filler materials

Phlegmatized dibenzoyl peroxide as a paste, filler materials

· Dangerous components:

100-42-5	styrene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-25%
94-36-0	dibenzoyl peroxide ⚠ Org. Perox. B, H241; ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	<2.5%
99-97-8	N,N-dimethyl-p-toluidine ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT RE 2, H373; Aquatic Chronic 3, H412	<1%

· **Additional information** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· Description of first aid measures

· **After inhalation** Take affected persons into the open air and position comfortably

· **After skin contact** Instantly wash with water and soap and rinse thoroughly. If skin irritation persists, call a physician.

· **After eye contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

· **After swallowing** Rinse out mouth and then drink plenty of water.

· Information for doctor

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

· Extinguishing media

· Suitable extinguishing agents

Water spray, carbon dioxide (CO₂), carbon dioxide blanket, foam, or dry powder.

Sand

· **For safety reasons unsuitable extinguishing agents** Water with full jet.

· Special hazards arising from the substance or mixture

Can be released in case of fire

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Nitrogen oxides (NO_x)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· Advice for firefighters

· Protective equipment:

In the event of fire, wear self contained breathing apparatus

EN 136 / EN 141 / EN 143



Trade name: Hilti OneStep Anchor HOS-C N30

(Contd. of page 2)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

- Wear protective clothing.

- Keep away from ignition sources

- **Environmental precautions:** Do not allow to enter the ground/soil.

- **Methods and material for containment and cleaning up:**

- Collect mechanically.

- Remove remainders with solvent and liquid-binding material.

- Dispose of contaminated material as waste according to item 13.

- Ensure adequate ventilation.

- **Reference to other sections**

- See Section 7 for information on safe handling

- See Section 8 for information on personal protection equipment.

- See Section 13 for information on disposal.

7 Handling and storage

- **Handling**

- **Precautions for safe handling**

- Observe expiry date.

- Keep ignition sources away - Do not smoke.

- Do not disassemble the OneStep bolt

- **Information about protection against explosions and fires:**

- keep away from heat and direct sunlight

- Keep ignition sources away - Do not smoke.

- **Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and containers:**

- Keep in a cool, dry and dark place; -20 °C to 25 °C.

- Please attend to the local storage regulations for underground mining operations

- **Information about storage in one common storage facility:** Store away from foodstuffs.

- **Further information about storage conditions:**

- Please attend to the local storage regulations for underground mining operations

- Protect from heat and direct sunlight.

- **Storage class 11**

- **Specific end use(s)** Rock anchor for stabilizing tunnels, galleries and the like.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

- The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

100-42-5 styrene	
NES	Short-term value: 426 mg/m ³ , 100 ppm
	Long-term value: 213 mg/m ³ , 50 ppm

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **Exposure controls**

- **Personal protective equipment**

- **General protective and hygienic measures**

- The usual precautionary measures should be adhered to general rules for handling chemicals.

- Do not eat, drink or smoke while working.

- Keep away from foodstuffs, beverages and food.

- Wash hands during breaks and at the end of the work.

- Avoid contact with the eyes and skin.

- Take off immediately all contaminated clothing

- **Breathing equipment:**

- Not required.

- In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

(Contd. on page 4)

Trade name: Hilti OneStep Anchor HOS-C N30

(Contd. of page 3)

- **Recommended filter device for short term use:** Filter AX
- **Protection of hands:**



Protective gloves

EN 374 / EN 388

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed safety glasses.

Face protection

- **Body protection:**



Protective work clothing.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: GRP-Bolt – integrated dual foil pack inside

Colour: foil package
grey-green-white

- **Odour:** Aromatic

- **Odour threshold:** Not determined.

- **pH-value:** Not applicable

- **Change in condition**

Melting point/Melting range: Not determined

Boiling point/Boiling range: Not determined

- **Flash point:** 31 °C (DIN 53213)

- **Inflammability (solid, gaseous)** Not determined.

- **Ignition temperature:** 480 °C

- **Decomposition temperature:** Not determined.

- **Self-inflammability:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive.

- **Critical values for explosion:**

Lower: 1.2 Vol % (Styrol)

Upper: 8.9 Vol % (Styrol)

- **Vapour pressure at 20 °C:** 7.1 hPa (Styrol)

- **Density** Not determined

- **Relative density** Not determined.

- **Vapour density** Not applicable.

(Contd. on page 5)

Trade name: Hilti OneStep Anchor HOS-C N30

(Contd. of page 4)

- | | |
|---|--|
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with Water: | Unsoluble |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| · dynamic: | Not applicable. |
| · kinematic: | Not applicable. |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Non-observance of the specified storage conditions (see section 7) will lead to gradual decomposition of the dibenzoylperoxide. This will make the product unusable.
To avoid thermal decomposition do not overheat.
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

100-42-5 styrene

Oral	LD50	5000 mg/kg (rat)
Inhalative	LC50/4h	24 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritant effect.
- **Sensitization:** Sensitization possible by skin contact.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **According to recipe contains the following heavy metals and compounds according to EC guideline NO. 76/464 EC:**
None
- **General notes:**
The product does not contain organically bounded halogens (AOX-free).
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

AUEN

(Contd. on page 6)

Trade name: Hilti OneStep Anchor HOS-C N30

(Contd. of page 5)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Unusable anchors must be collected separately. For disposal, local regulations issued by the authorities must be observed.
Consult the manufacturer if necessary.
For disposal, local regulations issued by the authorities must be observed.
Hand over to disposers of hazardous waste.
- **Uncleaned packagings:**
- **Recommendation:**
Non contaminated packagings can be reused.
Dispose of packaging according to regulations on the disposal of packagings.

14 Transport information

· UN-Number	
· ADG, ADN, IMDG, IATA	Void
· UN proper shipping name	
· ADG, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· ADG, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· ADG, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications. Assessment BAM Nr. II.2-1061 2/02 and Nr. II.2-324/03, Nr. II.2-135/09 Assessment BAM Nr. 2.2-109/13
· UN "Model Regulation":	-

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Australian Inventory of Chemical Substances		
All ingredients are listed.		
· Standard for the Uniform Scheduling of Drugs and Poisons		
100-42-5	styrene	S5
94-36-0	dibenzoyl peroxide	S2, S4, S5

- **National regulations**
- **Information about limitation of use:** Employment restrictions concerning young persons must be observed.
- **Chemical safety assessment:** not required.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H241 Heating may cause a fire or explosion.

(Contd. on page 7)

Trade name: Hilti OneStep Anchor HOS-C N30

(Contd. of page 6)

H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Hilti Entwicklungsgesellschaft mbH
Hiltistrasse 6
D-86916 Kaufering
Tel.: +49 8191 906310
Fax: +49 8191 90176310
e-mail: anchor.hse@hilti.com

· **Contact:** Mechthild Krauter

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

AU EN