

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date: 04/11/2021

Revision date: 04/11/2021

Supersedes: 18/01/2021

Version: 1.1

SECTION 1: Product identifier

1.1. Product identifier

Product form	Article
Trade name	DX-Cartridge Clean-Tec
Product code	BU Direct Fastening

1.2. Other means of identification

1.3. Recommended use of the chemical and restrictions on use

Recommended use	CARTRIDGES FOR TOOLS, BLANK
Restrictions on use	For professional use only

1.4. Supplier's details

Supplier

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
2138 Rhodes NSW - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

Department issuing data specification sheet:

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number	+61 2 8748 1000
------------------	-----------------

SECTION 2: Hazards identification

The dismantling of the article is prohibited!, This article contains hazardous substances or preparations not intended to be released under normal or reasonably foreseeable conditions of use.

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Explosives, Division 1.4	H204
--------------------------	------

2.2. Label elements

Hazard pictograms (GHS AU)



Signal word (GHS AU)

Warning

Hazard statements (GHS AU)

H204 - Fire or projection hazard.

Precautionary statements (GHS AU)

P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.

P250 - Do not subject to shock, friction, grinding.

P280 - Wear eye protection.

P372 - Explosion risk in case of fire.

P370+P380+P375 - In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

P401 - Store in accordance with local regulations on explosives.

2.3. Other hazards

Other hazards which do not result in classification

This article contains hazardous substances or preparations not intended to be released under normal or reasonably foreseeable conditions of use. The dismantling of the article is prohibited!. Keep away from ignition sources (including static discharges).

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 3: Composition/information on ingredients

Comments

max. net explosives weight each cartridge in mg:
 Caliber 6.8/11 (cal .27 short) white: 130; brown: 140; green: 160; yellow: 180; red: 230; titanium: 230; black: 260
 Caliber 6.8/18 (cal .27 long) green: 190; yellow: 220; blue: 300; red: 330; black: 410.
 Within the cartridges the explosive ingredients (gun powder and priming composition) are hermetically separated from the environment. They will be only opened with effort and under destruction of the article.
 Propellant powder: glycerol trinitrate containing nitrocellulose powder
 Mass per cartridge: essentially dependent on the required power (100-400 mg)
 Priming composition: SINTOX (initiating explosive) Mass per cartridge: 20,9 mg in the mean.
 Exposed propellant powder outside a cartridge is harmful if swallowed and highly flammable; without tamping no explosion risk.
 Packed safety cartridges don't represent a significant risk.
 In case of reaction no dangerous fragments or projectiles will be formed.
 Mechanical or thermal attempts to expose the primer composition lead to an immediate reaction of the dangerous ingredients.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
cellulose nitrate	9004-70-0	5 - 17	Not classified
glycerol trinitrate	55-63-0	2 - 7	Unst. Expl., H200 Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 STOT RE 2, H373 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
diphenylamine	122-39-4	0.1 - 1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT RE 2, H373
copper	7440-50-8	0 - 1	Aquatic Chronic 1, H410
zinc	7440-66-6	0 - 1	Not classified
tetrazene	109-27-3	0 - 1	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Symptoms caused by exposure

Symptoms/effects	Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Dry powder. Water spray.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures	Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
Hazardous decomposition products in case of fire	Carbon monoxide. Carbon dioxide (CO ₂). Nitrous gasses.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.
----------------------	---------------------------------

6.1.2. For emergency responders

Protective equipment	Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Pick up loose cartridges only by hand. Exposed ingredients must be swept up carefully and phlegmatized in a water container, labelled according the regulations, wipe down with water the contaminated area. Store away from other materials.
-------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	Hazardous waste due to potential risk of explosion.
Precautions for safe handling	Do not subject to grinding, shock, friction. Take precautionary measures against static discharge. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Store in a dry place.
Incompatible products	Strong bases. Strong acids.
Storage temperature	5 – 25 °C
Information on mixed storage	Keep away from : Ignition sources. Do not store with: Store according to local legislation.
Storage area	Store away from heat.

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

DX-Cartridge Clean-Tec	
Australia - Occupational Exposure Limits	
Local name	Copper
OES TWA [1]	0.2 mg/m ³ fume 1 mg/m ³ dusts & mists (as Cu)
OES TWA [2]	0.05 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
glycerol trinitrate (55-63-0)	
Australia - Occupational Exposure Limits	
Local name	Nitroglycerin (NG)
OES TWA [1]	0.46 mg/m ³
OES TWA [2]	0.05 ppm
diphenylamine (122-39-4)	
Australia - Occupational Exposure Limits	
Local name	Diphenylamine
OES TWA [1]	10 mg/m ³

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

No additional information available

8.4. Personal protective equipment

Personal protective equipment	When using cartridge operated tools, sufficient ear protection must be worn.
Eye protection	Safety glasses
Skin and body protection	When using cartridge operated tools, sufficient ear protection must be worn.
Personal protective equipment symbol(s)	



Other information

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	No data available
Colour	No data available
Odour	No data available
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative density	No data available
Density	No data available
Solubility	No data available
Partition coefficient n-octanol/water (Log Pow)	No data available
Explosive properties	Fire or projection hazard.
Explosive limits	No data available
Minimum ignition energy	No data available
Fat solubility	No data available
Additional information	Not applicable. Article

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Not established.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	Carbon monoxide. Carbon dioxide. Nitrogen oxides. Metal oxides. Thermal decomposition can lead to the release of irritating gases and vapours.

SECTION 11: Toxicological information

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

glycerol trinitrate (55-63-0)	
LD50 oral rat	685 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	685 mg/kg
LD50 dermal rat	> 9560 mg/kg bodyweight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Dermal)
diphenylamine (122-39-4)	
LD50 oral rat	> 800 mg/kg bodyweight (Rat, Male, Experimental value, Oral)
zinc (7440-66-6)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Not classified
Respiratory or skin sensitisation	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available. No harmful effects are to be expected if used properly. The contained ingredients can be harmful, but they are hermetically enclosed in the article and can not be released. The dismantling of the article is prohibited.

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	No harmful effects are to be expected if used properly. The contained ingredients can be harmful, but they are hermetically enclosed in the article and can not be released. The dismantling of the article is prohibited.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Other information	Avoid release to the environment.

glycerol trinitrate (55-63-0)	
LC50 - Fish [1]	1.9 mg/l (ASTM E729-80, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Lethal)
NOEC chronic fish	0.03 mg/l
diphenylamine (122-39-4)	
EC50 - Crustacea [1]	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	2.17 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Experimental value, GLP)
NOEC chronic algae	0.0273 mg/l
BCF - Fish [1]	51 – 253 (Cyprinus carpio, Literature study, Test duration: 8 weeks)
Partition coefficient n-octanol/water (Log Pow)	3.71 – 3.84 (Weight of evidence approach, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20.2 °C)
Partition coefficient n-octanol/water (Log Koc)	2.818 – 2.917 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
copper (7440-50-8)	
LC50 - Fish [1]	200 µg/l (96 h, Salmo gairdneri, Flow-through system, Fresh water, Weight of evidence, Lethal)
EC50 - Crustacea [1]	109 – 798 µg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Weight of evidence, Locomotor effect)
zinc (7440-66-6)	
LC50 - Fish [1]	0.169 mg/l (Other, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Read-across, Zinc ion)
EC50 - Crustacea [1]	416 µg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Ceriodaphnia dubia, Static system, Fresh water, Experimental value)
ErC50 algae	0.15 mg/l
BCF - Fish [1]	0.002 (40 day(s), Danio rerio, Semi-static system, Fresh water, Read-across)
tetrazene (109-27-3)	
EC50 - Crustacea [1]	0.14 mg/l

12.2. Persistence and degradability

DX-Cartridge Clean-Tec	
Persistence and degradability	Not established.
glycerol trinitrate (55-63-0)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

glycerol trinitrate (55-63-0)	
Biochemical oxygen demand (BOD)	53.6 g O ₂ /g substance
diphenylamine (122-39-4)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
ThOD	2.39 g O ₂ /g substance
copper (7440-50-8)	
Not rapidly degradable	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
zinc (7440-66-6)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
tetrazene (109-27-3)	
Not rapidly degradable	

12.3. Bioaccumulative potential

DX-Cartridge Clean-Tec	
Bioaccumulative potential	Not established.
glycerol trinitrate (55-63-0)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
diphenylamine (122-39-4)	
BCF - Fish [1]	51 – 253 (Cyprinus carpio, Literature study, Test duration: 8 weeks)
Partition coefficient n-octanol/water (Log Pow)	3.71 – 3.84 (Weight of evidence approach, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20.2 °C)
Partition coefficient n-octanol/water (Log Koc)	2.818 – 2.917 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
copper (7440-50-8)	
Bioaccumulative potential	Bioaccumulation: not applicable.
zinc (7440-66-6)	
BCF - Fish [1]	0.002 (40 day(s), Danio rerio, Semi-static system, Fresh water, Read-across)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

glycerol trinitrate (55-63-0)	
Ecology - soil	Low potential for adsorption in soil.
diphenylamine (122-39-4)	
Surface tension	71.8 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Pow)	3.71 – 3.84 (Weight of evidence approach, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20.2 °C)
Partition coefficient n-octanol/water (Log Koc)	See section 12.1 on ecotoxicology 2.818 – 2.917 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
copper (7440-50-8)	
Ecology - soil	Adsorbs into the soil.
zinc (7440-66-6)	
Surface tension	No data available in the literature

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

zinc (7440-66-6)	
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

DX-Cartridge Clean-Tec	
Fluorinated greenhouse gases	False
glycerol trinitrate (55-63-0)	
Fluorinated greenhouse gases	False
diphenylamine (122-39-4)	
Fluorinated greenhouse gases	False
cellulose nitrate (9004-70-0)	
Fluorinated greenhouse gases	False
copper (7440-50-8)	
Fluorinated greenhouse gases	False
zinc (7440-66-6)	
Fluorinated greenhouse gases	False
tetrazene (109-27-3)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Refer to manufacturer/supplier for information on recovery/recycling.
Additional information	Cartridge strips with unused cartridges: Hazardous waste due to risk of explosion. European waste catalogue: 16 04 01* - waste ammunition. If possible use up the cartridges or store them for your next project. If not possible to use up the cartridges - The strip is mixed municipal waste and the cartridge itself is "waste ammunition" and has to be disposed of by an authorized/certified company. If cartridges are used up: European waste catalogue: 20 03 01 - mixed municipal waste . The product (cartridges and strip) can be disposed of as household or factory waste.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 0014	UN 0014	UN 0014	UN 0014
14.2. UN proper shipping name			
CARTRIDGES FOR TOOLS, BLANK	CARTRIDGES FOR TOOLS, BLANK	Cartridges for tools, blank	CARTRIDGES FOR TOOLS, BLANK
Transport document description			
UN 0014 CARTRIDGES FOR TOOLS, BLANK, 1.4S, (E)	UN 0014 CARTRIDGES FOR TOOLS, BLANK, 1.4S	UN 0014 Cartridges for tools, blank, 1.4S	UN 0014 CARTRIDGES FOR TOOLS, BLANK, 1.4S
14.3. Transport hazard class(es)			
1.4S	1.4S	1.4S	1.4S

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

ADR	IMDG	IATA	RID
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	1.4S
Special provisions (ADR)	364
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P130, LP101
Mixed packing provisions (ADR)	MP23, MP24
Transport category (ADR)	4
Tunnel restriction code (ADR)	E

Transport by sea

Special provisions (IMDG)	364
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	P130
EmS-No. (Fire)	F-B
EmS-No. (Spillage)	S-X
Stowage category (IMDG)	01
Stowage and handling (IMDG)	SW1
MFAG-No	114

Air transport

PCA packing instructions (IATA)	130
PCA max net quantity (IATA)	25kg
Special provisions (IATA)	A802

Rail transport

Special provisions (RID)	364
Limited quantities (RID)	5kg
Packing instructions (RID)	P130, LP101

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8. Hazchem or Emergency Action Code

Hazchem Code Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
2.2	Precautionary statements (GHS AU)	Modified	
3.2	Composition/information on ingredients	Modified	

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE - Acute Toxicity Estimate
 BCF - Bioconcentration factor
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 DMEL - Derived Minimal Effect level
 DNEL - Derived-No Effect Level
 EC50 - Median effective concentration
 IARC - International Agency for Research on Cancer
 IATA - International Air Transport Association
 IMDG - International Maritime Dangerous Goods
 LC50 - Median lethal concentration
 LD50 - Median lethal dose
 LOAEL - Lowest Observed Adverse Effect Level
 NOAEC - No-Observed Adverse Effect Concentration
 NOAEL - No-Observed Adverse Effect Level
 NOEC - No-Observed Effect Concentration
 OECD - Organisation for Economic Co-operation and Development
 PBT - Persistent Bioaccumulative Toxic
 PNEC - Predicted No-Effect Concentration
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS - Safety Data Sheet
 vPvB - Very Persistent and Very Bioaccumulative

04/11/2021

Revision date

Classification:

Expl. 1.4	H204
-----------	------

Full text of H-statements:

Acute Tox. 1 (Dermal)	Acute toxicity (dermal), Category 1
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 2	Hazardous to the aquatic environment — Acute Hazard, Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Expl. 1.4	Explosives, Division 1.4
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2

DX-Cartridge Clean-Tec

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Unst. Expl.	Explosives, Unstable explosives
H200	Unstable explosives.
H204	Fire or projection hazard.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

SDS_AU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.