HIT-HY 170

en	This safety data sheet file is issued for the following production lots: 1. Version 2.X is valid for HIT-HY 170 with a maximum expiration date of 12/2022 (see foil pack manifold) 2. Version 3.0 is valid for HIT-HY 170 with a minimum expiration date of 01/2023 (see the foil pack manifold)
de	Diese Sicherheitsdatenblatt-Datei betrifft die folgenden Fertigungslose: 1. Version 2.X ist gültig für HIT-HY 170 mit einem Haltbarkeitsdatum bis 12/2022 (siehe Verbindungsteil) 2. Version 3.0 ist gültig für HIT-HY 170 mit einem Haltbarkeitsdatum ab 01/2023 (siehe Verbindungsteil)
nl	Dit veiligheidsinformatiebladbestand wordt afgegeven voor de volgende productie-lots: 1. Versie 2.X is geldig voor HIT-HY 170 met een maximale houdbaarheidsdatum tot 12/2022 (zie foliepak verdeler) 2. Versie 3.0 is geldig voor HIT-HY 170 met een minimale houdbaarheidsdatum tot 01/2023 (zie foliepak verdeler)
fr	Ce fichier de données de sécurité est délivré pour les lots de production suivants : 1. La version 2.X est valide pour HIT-HY 170 avec une date d'expiration maximale de 12/2022 (voir le raccord de cartouche souple) 2. La version 3.0 est valide pour HIT-HY 170 avec une date d'expiration maximale de 01/2023 (voir le raccord de cartouche souple)
da	Denne sikkerhedsdatabladsfil er udgivet for følgende produktions lots: 1. Version 2.X er gældende for HIT-HY 170 med en maksimal udløbsdato d. 12/2022 (se foliepakkens manifold) 2. Version 3.0 er gældende for HIT-HY 170 med en mindste udløbsdato d. 01/2023 (se foliepakkens manifold)
sv	Denna säkerhetsdatabladsfil har utfärdats för följande tillverkningspartier: 1. Version 2.X är giltig för HIT-HY 170 med ett sista giltighetsdatum den 12/2022 (se folieförpackningens grenrör) 2. Version 3.0 är giltig för HIT-HY 170 med ett första giltighetsdatum den 01/2023 (se folieförpackningens grenrör)
fi	Tämä käyttöturvallisuustiedote koskee seuraavia tuotantoeriä: 1. Versio 2.X koskee HIT-HY 170 -tuotetta, jonka viimeinen käyttöpäivämäärä on 12/2022 tai sitä ennen (ks. foliopakkauksen taite) 2. Versio 3.0 koskee HIT-HY 170 -tuotetta, jonka viimeinen käyttöpäivämäärä on 01/2023 tai sen jälkeen (ks. foliopakkauksen taite)
hu	Ezt a biztonsági adatlapot a következő gyártási tételekhez bocsátják ki: 1. Az 2.X változat legfeljebb 2022/12 lejárati dátummal érvényes a HIT-HY 170-re (lásd a fóliacsomag sokszorosított iratát) 2. Az 3.0 változat legalább 2023/01 lejárati dátummal érvényes a HIT-HY 170-re (lásd a fóliacsomag sokszorosított iratát)
es	Este archivo de hoja de datos de seguridad se emite para los siguientes lotes de producción: 1. Versión 2.X válida para HIT-HY 170 con una fecha de caducidad máxima de 12/2022 (consulte el colector de láminas) 2. Versión 3.0 válida para HIT-HY 170 con una fecha de caducidad mínima de 01/2023 (consulte el colector de láminas)
pt	Este ficheiro com ficha de dados de segurança é emitido para os seguintes lotes de produção: 1. A versão 2.X é válida para a HIT-HY 170 com um prazo máximo de validade até 12/2022 (ver as diversas embalagens) 2. A versão 3.0 é válida para a HIT-HY 170 com um prazo mínimo de validade até 01/2023 (ver as diversas embalagens)
it	Questo file della scheda tecnica di sicurezza è rilasciato per i seguenti lotti di produzione: 1. La versione 2.X è valida per HIT-HY 170 con data di scadenza massima 12/2022 (vedere la giunzione della confezione) 2. La versione 3.0 è valida per HIT-HY 170 con data di scadenza minima 01/2023 (vedere la giunzione della confezione)
pl	Ten plik arkusza danych bezpieczeństwa jest wydany dla następujących części produkcyjnych: 1. Wersja 2.X obowiązuje w przypadku HIT-HY 170 z maksymalnym dniem rozpoczęcia pracy 12/2022 (patrz opakowanie foliowe) 2. Wersja 3.0 obowiązuje w przypadku HIT-HY 170 z minimalnym dniem rozpoczęcia pracy 01/2023 (patrz opakowanie foliowe)
ru	Этот файл сертификата безопасности предоставлен для следующих партий продукции: 1. Версия 2.X действительна для HIT-HY 170 с максимальным сроком годности до 12.2022 г. (см. присоединительную часть на капсуле) 2. Версия 3.0 действительна HIT-HY 170 с минимальным сроком годности до 01.2023 г. (см. присоединительную часть на капсуле)
el	Το παρόν δελτίο δεδομένων ασφάλειας εκδίδεται για τις ακόλουθες παρτίδες παραγωγής: 1. Η έκδοση 2.X ισχύει για το HIT-HY 170 με μέγιστη ημερομηνία λήξης τον 12/2022 (βλέπε διανομέα συσκευασίας μεμβράνης) 2. Η έκδοση 3.0 ισχύει για το HIT-HY 170 με ελάχιστη ημερομηνία λήξης τον 01/2023 (βλέπε τον διανομέα της συσκευασίας μεμβράνης)
cs	Tento soubor s bezpečnostním listem je vystaven pro tyto výrobní závody 1. Verze 2.X je platná pro HIT-HY 170 s maximálním datem expirace 12/2022 (viz fólie balení) 2. Verze 3.0 je platná pro HIT-HY 170 s minimálním datem expirace 01/2023 (viz fólie balení)
bg	Този информационен лист за безопасност се публикува за следните производствени партиди: 1. Версия 2.X е валидна за HIT-HY 170 с максимален срок на валидност до 12.2022 г. (вж. фолийна опаковка за колектор) 2. Версия 3.0 е валидна за HIT-HY 170 с минимален срок на изтичане 01.2023 г. (вж. фолийна опаковка за колектор)
lv	Šo drošības datu lapa ir izsniegta šādām ražojumu partijām: 1. Versija 2.X ir derīga izstrādājumam HIT-HY 170, kura maksimālais derīguma termiņš ir 2022. gada maijs (skatīt folija iepakojuma kolektoru) 2. Versija 3.0 ir derīga izstrādājumam HIT-HY 170, kura minimālais derīguma termiņš ir 2023. gada jūnijs (skatīt folija iepakojuma kolektoru)
lt	Šis saugos duomenų lapo failas išduodamas šioms gamybos partijoms: 1. 2.X versija galioja HIT-HY 170, kurios maksimali galiojimo data – 2022-12 (žr. folinių pakuočių rinkinį) 2. 3.0 versija galioja HIT-HY 170, kurios minimali galiojimo data – 2023-01 (žr. folinių pakuočių rinkinį)
sk	Tento súbor bezpečnostných údajov sa vydáva pre tieto výrobné šarže: 1. Verzia 2.X je platná pre HIT-HY 170 s maximálnym dátumom exspirácie 12/2022 (pozrite si údaj na fólii balenia) 2. Verzia 3.0 je platná pre HIT-HY 170 s minimálnym dátumom exspirácie 01/2023 (pozrite si údaj na fólii balenia)
sl	Datoteka z varnostnim listom je izdana za naslednje proizvodne serije: 1. Različica 2.X je veljavna za izdelek HIT-HY 170 z maksimalnim datumom poteka veljavnosti: 12/2022 (glejte pakiranje) 2. Različica 3.0 je veljavna za izdelek HIT-HY 170 z minimalnim datumom poteka veljavnosti: 01/2023 (glejte pakiranje)

HIT-HY 170

et	See ohutuskaardi fail on välja antud järgmistele tootepartiidele: 1. Versioon 2.X kehtib tootele HIT-HY 170 viimase säilimiskuupäevaga 12/2022 (vt fooliumpakendi hargnemiskohta) 2. Versioon 3.0 kehtib tootele HIT-HY 170 esimese säilimiskuupäevaga 01/2023 (vt fooliumpakendi hargnemiskohta)
ro	Acest fișier cu date tehnice de securitate este emis pentru următoarele locuri de producție: 1. Versiunea 2.X este valabilă pentru HIT-HY 170 cu data maximă de expirare 12/2022 (a se vedea racordul pentru cartușe din folie) 2. Versiunea 3.0 este valabilă pentru HIT-HY 170 cu data minimă de expirare 01/2023 (a se vedea racordul pentru cartușe din folie)
hr	Ovaj sigurnosno-tehnički list izdaje se za sljedeće proizvodne serije: 1. Verzija 2.X vrijedi za HIT-HY 170 s maksimalnim rokom trajanja do 12/2022 (vidjeti razvodnik iz folije) 2. Verzija 3.0 vrijedi za HIT-HY 170 s minimalnim rokom trajanja do 01/2023 (vidjeti razvodnik iz folije)
tr	Bu güvenlik bilgi formu dosyası aşağıdaki üretim partileri için hazırlanmıştır: 1. Versiyon 2.X, maksimum son kullanma tarihi 12/2022 olan HIT-HY 170 için geçerlidir (bkz. folyo paketi manifoldu) 2. Versiyon 3.0, inimumm son kullanma tarihi 01/2023 olan HIT-HY 170 için geçerlidir (bkz. folyo paketi manifoldu)
uk	Цей файл сертифіката безпеки надано для наступних партій продукції: 1. Версія 2.X дійсна для HIT-HY 170 з максимальним терміном придатності до 12.2022 р. (див. приєднувальну частину на капсулі) 2. Версія 3.0 дійсна для HIT-HY 170 з мінімальним терміном придатності до 01.2023 р. (див. приєднувальну частину на капсулі)
zh	**本安全数据表文件**针对以下生产批次发布： 1. **版本** 2.X 对 HIT-HY 170 **有效，最**长失效日期为 2022 **年** 12 **月**（**参**见箔包装歧管） 2. **版本** 3.0 对 HIT-HY 170 **有效，最短失效日期**为 2023 **年** 1 **月**（**参**见箔包装歧管）
ar	يتم إصدار ملف صحيفة بيانات السلامة لتشغيلات الإنتاج التالية: 1. الإصدار 2.X صالح لـ HIT-HY 170 بحد أقصى لتاريخ انتهاء الصلاحية هو 2022/12 (انظر العبوة المصنوعة من رقائق الألومنيوم) 2. الإصدار 3.0 صالح لـ HIT-HY 170 على الأقل لتاريخ انتهاء الصلاحية هو 2023/1 (انظر العبوة المصنوعة من رقائق الألومنيوم)
ja	この安全性データシートファイルは、次の生産ロット用に発行されています： 1. バージョン 2.X は、有効期限が最大 2022 年 12 月までの HIT-HY 170 に対して有効です (フォイルパック連結部に表示) 2. バージョン 3.0 は、有効期限が 2023 年 1 月以降の HIT-HY 170 に対して有効です (フォイルパック連結部に表示)
sr	Datoteka bezbednosnog lista se izdaje za sledeće proizvodne serije: 1. Verzija 2.X je dostupna za HIT-HY 170 sa maksimalnim datumom isteka 12/2022 (pogledajte ivicu pakovanja od folije) 2. Verzija 3.0 je dostupna za HIT-HY 170 sa minimalnim datumom isteka 01/2023 (pogledajte ivicu pakovanja od folije)
ms	Fail helaian data keselamatan ini dikeluarkan untuk lot pengeluaran yang berikut: 1. Versi 2.X adalah sah untuk HIT-HY 170 dengan tarikh tamat tempoh maksimum pada 12/2022 (lihat manifold pek kerajang) 2. Versi 3.0 adalah sah untuk HIT-HY 170 dengan tarikh tamat tempoh minimum pada 01/2023 (lihat manifold pek kerajang)
ko	본 안전보건자료는 다음 제품 로트에 대해 발급되었습니다. 1. 버전 2.X(은)는 HIT-HY 170에 대해 유효하며, 최대 만료 기한은 2022년 12월입니다(호일 팩 매니폴드 참조) 2. 버전 3.0(은)는 HIT-HY 170에 대해 유효하며, 최소 만료 기한은 2023년 1월입니다(호일 팩 매니폴드 참조)
id	File lembar data keselamatan ini diterbitkan untuk lot produksi berikut: 1. Versi 2.X berlaku untuk HIT-HY 170 dengan tanggal kedaluwarsa maksimum 12/2022 (lihat foil pack manifold) 2. Versi 3.0 berlaku untuk HIT-HY 170 dengan tanggal kedaluwarsa minimum 01/2023 (lihat foil pack manifold)
he	קובץ גיליון נתוני בטיחות זה מונפק עבור מגרשי הייצור הבאים: 1. גרסה 2.X תקפה ל-HIT-HY 170 עם תאריך תפוגה מקסימלי של 12/2022 (ראה יריעת foil pack) 2. גרסה 3.0 תקפה ל-HIT-HY 170 עם תאריך תפוגה מינימלי של 01/2023 (ראה יריעת foil pack)
th	แผ่นข้อมูลด้านความปลอดภัยนี้ที่ได้จัดทำสำหรับล็อตการผลิตดังต่อไปนี้: 1. เวอร์ชั่น 2.X ใช้ได้กับ HIT-HY 170 ที่มีวันหมดอายุไม่เกิน 12/2022 (โปรดดูแผ่นพับห่อฟอยล์) 2. เวอร์ชั่น 3.0 ใช้ได้กับ HIT-HY 170 ที่มีวันหมดอายุขั้นต่ำ 01/2023 (โปรดดูแผ่นพับห่อฟอยล์)
vi	Tệp bảng dữ liệu an toàn này được phát hành cho các lô sản xuất sau: 1. Phiên bản 2.X hợp lệ cho HIT-HY 170 với ngày hết hạn tối đa là 12/2022 (xem ống keo cấy thép) 2. Phiên bản 3.0 hợp lệ cho HIT-HY 170 với ngày hết hạn tối thiểu là 01/2023 (xem ống keo cấy thép)
zh tw	**下列生**產批次將獲核發本安全資料表檔案： 1. 2.X **版適用於** HIT-HY 170，**最長到期日** 12/2022 (**請見**鋁箔包打字紙) 2. 3.0 **版適用於** HIT-HY 170，**最短到期日** 01/2023 (**請見**鋁箔包打字紙)
kk	Бұл қауіпсіздік паспорты мына өндірістік партиялар үшін шығарылады: 1. 2.X нұсқасы жарамдылық мерзімі көп уақытты (12/2022) қамтитын HIT-HY 170 үшін жарамды (жұқалтыр қаптаманы қараңыз) 2. 3.0 нұсқасы жарамдылық мерзімі аз уақытты (01/2023) қамтитын HIT-HY 170 үшін жарамды (жұқалтыр қаптаманы қараңыз)

HIT-HY 170

Safety information for 2-Component-products

Issue date: 22/09/2021 Revision date: 22/09/2021 Supersedes: 22/03/2020 Version: 3.0

SECTION 1: Kit identification

1.1 Product identifier

Product name HIT-HY 170

Product code BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
2138 Rhodes NSW - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

SECTION 2: General information

Storage Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3:

Classification of the Product

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317

2.2. Label elements

Hazard pictograms (GHS AU)

GHS07

Signal word (GHS AU)	Warning
Hazard statements (GHS AU)	H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.
Precautionary statements (GHS AU)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P302+P352 - IF ON SKIN: Wash with plenty of water/... P337+P313 - If eye irritation persists: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards not contributing to the classification

No additional information available

Additional information

2-Component-foilpack, contains:
Component A: Urethane methacrylate resin, inorganic filler
Component B: Dibenzoyl peroxide, phlegmatized



Name	General description	Quantity	Unit	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
HIT-HY 170, B		1	pcs (pieces)	Skin Sens. 1, H317
HIT-HY 170, A		1	pcs (pieces)	Eye Irrit. 2A, H319 Skin Sens. 1, H317

SECTION 4: General advice

General advice — For professional users only

SECTION 5: Safe handling advice

General measures — Spilled material may present a slipping hazard

Environmental precautions — Prevent entry to sewers and public waters
Notify authorities if liquid enters sewers or public waters

Storage conditions — Keep cool. Protect from sunlight.

Precautions for safe handling — Wear personal protective equipment
Avoid contact with skin and eyes
Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
Provide good ventilation in process area to prevent formation of vapour

Methods for cleaning up — This material and its container must be disposed of in a safe way, and as per local legislation
Mechanically recover the product
Store away from other materials.

For containment — Collect spillage.

Incompatible materials — Sources of ignition
Direct sunlight

Incompatible products — Strong bases
Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact — Rinse immediately with plenty of water
Remove contact lenses, if present and easy to do. Continue rinsing.
Obtain medical attention if pain, blinking or redness persists

First-aid measures after ingestion — Rinse mouth
Get medical advice/attention.
Do not induce vomiting
Obtain emergency medical attention

First-aid measures after inhalation — Remove person to fresh air and keep comfortable for breathing.
Allow affected person to breathe fresh air
Allow the victim to rest

First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects after eye contact	May cause severe irritation
Symptoms/effects after skin contact	May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 170, A

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date: 22/09/2021 Revision date: 22/09/2021 Supersedes: 12/02/2020 Version: 3.0

SECTION 1: Product identifier

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 170, A
Product code	BU Anchor

1.2. Other means of identification

1.3. Recommended use of the chemical and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.4. Supplier's details

Supplier
Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
2138 Rhodes NSW - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

Department issuing data specification sheet:
Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number	+61 2 8748 1000

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317

2.2. Label elements

Hazard pictograms (GHS AU)

Signal word (GHS AU)	Warning
Contains	2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (10 – 25 %); 2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (1 – 2.5 %)
Hazard statements (GHS AU)	H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.
Precautionary statements (GHS AU)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P302+P352 - IF ON SKIN: Wash with plenty of water/... P337+P313 - If eye irritation persists: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	27813-02-1	10 – 25	Eye Irrit. 2A, H319 Skin Sens. 1, H317
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	2082-81-7	1 – 2.5	Skin Sens. 1B, H317
1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3	0.1 – 1	Acute Tox. 2 (Oral), H300 Eye Irrit. 2A, H319

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general: Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact: Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion: Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Symptoms caused by exposure

Symptoms/effects after skin contact: May cause an allergic skin reaction.

Symptoms/effects after eye contact: May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Water spray. Carbon dioxide. Dry powder. Foam. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures: Spilled material may present a slipping hazard.

Hazardous decomposition products in case of fire: Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting: Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures: Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls	Ensure adequate ventilation.

8.4. Personal protective equipment

Personal protective equipment	Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.
Hand protection	Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection	Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection — Wear suitable protective clothing

Personal protective equipment symbol(s)

Environmental exposure controls — Avoid release to the environment.

Consumer exposure controls — Avoid contact during pregnancy/while nursing.

Other information — Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	No data available
Odour	No data available
Odour threshold	Not determined
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	> 109 °C DIN EN ISO 1523
Auto-ignition temperature	Not self-igniting
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative density	No data available
Density	Density : 1.65 g/ml AW 4.3.23
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	60606.061 mm²/s
Viscosity, dynamic	100 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available
Minimum ignition energy	No data available
Fat solubility	No data available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LD50 oral rat	25 mg/kg
LD50 dermal rat	> 2000 mg/kg

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 170, A	
Viscosity, kinematic	60606.061 mm²/s

Potential adverse human health effects and symptoms	No additional information available

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Other information	Avoid release to the environment.

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LC50 - Fish [1]	≈ 17 mg/l
LC50 - Other aquatic organisms [1]	245 mg/l
EC50 - Crustacea [1]	28.8 mg/l
NOEC (acute)	57.8 mg/l
Partition coefficient n-octanol/water (Log Kow)	2.1

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l
NOEC (acute)	7.51 mg/l
NOEC (chronic)	20 mg/l
Partition coefficient n-octanol/water (Log Pow)	3.1

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Partition coefficient n-octanol/water (Log Koc)	1.9 (log Koc, Calculated value)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

12.2. Persistence and degradability

HIT-HY 170, A	
Persistence and degradability	Not established.

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Not rapidly degradable	
Biodegradation	84 %

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-HY 170, A	
Bioaccumulative potential	Not established.

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Partition coefficient n-octanol/water (Log Kow)	2.1

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Partition coefficient n-octanol/water (Log Koc)	1.9 (log Koc, Calculated value)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

12.4. Mobility in soil

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Partition coefficient n-octanol/water (Log Kow)	2.1

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Pow)	3.1

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Partition coefficient n-octanol/water (Log Pow)	0.97 (OECD 102 method)
Partition coefficient n-octanol/water (Log Koc)	See section 12.1 on ecotoxicology1.9 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone — Not classified

Other adverse effects — No additional information available

HIT-HY 170, A	
Fluorinated greenhouse gases	False

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Fluorinated greenhouse gases	False

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Fluorinated greenhouse gases	False

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

Overland transport
Not applicable

Transport by sea
Not applicable

Air transport
Not applicable

Rail transport
Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8. Hazchem or Emergency Action Code

Hazchem Code: Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:
Hazards identification. Composition/information on ingredients. Modified.

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE - Acute Toxicity Estimate

BCF - Bioconcentration factor

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DMEL - Derived Minimal Effect level

DNEL - Derived-No Effect Level

vPvB - Very Persistent and Very Bioaccumulative

SDS - Safety Data Sheet

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

PNEC - Predicted No-Effect Concentration

PBT - Persistent Bioaccumulative Toxic

OECD - Organisation for Economic Co-operation and Development

NOEC - No-Observed Effect Concentration

NOAEL - No-Observed Adverse Effect Level

NOAEC - No-Observed Adverse Effect Concentration

LOAEL - Lowest Observed Adverse Effect Level

LD50 - Median lethal dose

LC50 - Median lethal concentration

IMDG - International Maritime Dangerous Goods

IATA - International Air Transport Association

EC50 - Median effective concentration

IARC - International Agency for Research on Cancer

Revision date: 22/09/2021

Other information: None.

Classification:

Eye Irrit. 2A	H319
Skin Sens. 1	H317

Full text of H-statements:

Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H300	Fatal if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

HIT-HY 170, A

Safety Data Sheet

according to the Model Work Health and Safety Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 170, B

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date: 22/09/2021 Revision date: 22/09/2021 Supersedes: 23/03/2020 Version: 1.4

SECTION 1: Product identifier

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 170, B
Product code	BU Anchor

1.2. Other means of identification

1.3. Recommended use of the chemical and restrictions on use

Recommended use	Composite mortar component for fasteners in the construction industry
Restrictions on use	For professional use only

1.4. Supplier's details

Supplier
Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
2138 Rhodes NSW - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

Department issuing data specification sheet:
Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number	+61 2 8748 1000

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Skin sensitisation, Category 1 H317

2.2. Label elements

Hazard pictograms (GHS AU)

Signal word (GHS AU)	Warning
Contains	dibenzoyl peroxide (5 - 10 %)
Hazard statements (GHS AU)	H317 - May cause an allergic skin reaction.
Precautionary statements (GHS AU)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P302+P352 - IF ON SKIN: Wash with plenty of water/... P337+P313 - If eye irritation persists: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
dibenzoyl peroxide	94-36-0	5 - 10	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general: Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact: Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion: Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Symptoms caused by exposure

Symptoms/effects after skin contact: May cause an allergic skin reaction.

Symptoms/effects after eye contact: May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Water spray. Carbon dioxide. Dry powder. Foam. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures: Spilled material may present a slipping hazard.

Hazardous decomposition products in case of fire: Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting: Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures: Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment: Use personal protective equipment as required. Equip cleanup crew with proper protection.

Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

HIT-HY 170, B	
Australia - Occupational Exposure Limits	
Local name	Benzoyl peroxide (Dibenzoyl peroxide)
OES TWA [1]	5 mg/m³
Remark (AU)	Sen - Respiratory and/or Skin Sensitiser.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

Additional information: The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls: Ensure adequate ventilation.

8.4. Personal protective equipment

Personal protective equipment: Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection: Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection: Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection: Wear suitable protective clothing

Personal protective equipment symbol(s)

Environmental exposure controls: Avoid release to the environment.

Consumer exposure controls: Avoid contact during pregnancy/while nursing.

Other information: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	No data available
Odour	No data available
Odour threshold	Not determined
pH	≈ 6
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	Not self-igniting
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative density	No data available
Density	Density : 1.7 g/cm³ DIN 51757
Solubility	Water: Not miscible
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, kinematic	52941.176 mm²/s
Viscosity, dynamic	90 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available
Minimum ignition energy	No data available
SADT	65 °C
Fat solubility	No data available

SECTION 10: Stability and reactivity

Reactivity	No additional information available
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.

Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified pH: ≈ 6
Serious eye damage/irritation	Not classified pH: ≈ 6
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 170, B	
Viscosity, kinematic	52941.176 mm²/s

Potential adverse human health effects and symptoms	No additional information available

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Other information	Avoid release to the environment.

dibenzoyl peroxide (94-36-0)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)
NOEC chronic fish	0.001 mg/l
Partition coefficient n-octanol/water (Log Pow)	3.71
Partition coefficient n-octanol/water (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)

12.2. Persistence and degradability

HIT-HY 170, B	
Persistence and degradability	Not established.

dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-HY 170, B	
Bioaccumulative potential	Not established.

dibenzoyl peroxide (94-36-0)	
Partition coefficient n-octanol/water (Log Pow)	3.71
Partition coefficient n-octanol/water (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Partition coefficient n-octanol/water (Log Pow)	3.71
Partition coefficient n-octanol/water (Log Koc)	See section 12.1 on ecotoxicology3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

Ozone: Not classified

Other adverse effects: No additional information available

HIT-HY 170, B	
Fluorinated greenhouse gases	False

dibenzoyl peroxide (94-36-0)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste): Disposal must be done according to official regulations.

Product/Packaging disposal recommendations: After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)

ADR	IMDG	IATA	RID
Transport document description			
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III
14.3. Transport hazard class(es)			
9	9	9	9
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	M7
Special provisions (ADR)	274, 335, 375, 601
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	
Tunnel restriction code (ADR)	-

Transport by sea

Special provisions (IMDG)	274, 335, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23

Air transport

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)	274, 335, 375, 601
Limited quantities (RID)	5kg

Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8. Hazchem or Emergency Action Code

Hazchem Code	Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status	All the chemicals contained in this product are listed introductions

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:
Transport information. Added.

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE - Acute Toxicity Estimate

BCF - Bioconcentration factor

DMEL - Derived Minimal Effect level

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DNEL - Derived-No Effect Level

EC50 - Median effective concentration

IARC - International Agency for Research on Cancer

IATA - International Air Transport Association

IMDG - International Maritime Dangerous Goods

LC50 - Median lethal concentration

LD50 - Median lethal dose

LOAEL - Lowest Observed Adverse Effect Level

NOAEC - No-Observed Adverse Effect Concentration

NOAEL - No-Observed Adverse Effect Level

SDS - Safety Data Sheet

vPvB - Very Persistent and Very Bioaccumulative

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

PNEC - Predicted No-Effect Concentration

PBT - Persistent Bioaccumulative Toxic

Revision date	22/09/2021
Other information	None.

Classification:

Skin Sens. 1	H317

Full text of H-statements:

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Org. Perox. B	Organic Peroxides, Type B

Skin Sens. 1	Skin sensitisation, Category 1
H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

SDS_AU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 170

Safety information for 2-Component-products

Issue date: 23/03/2020 Revision date: 22/03/2020 Supersedes: 19/11/2018 Version: 2.0

SECTION 1: Kit identification

1.1 Product identifier

Product name	HIT-HY 170
	
Product code	BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
2138 Rhodes NSW - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

SECTION 2: General information

Storage	Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3:

Classification of the Product

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1B	H350

2.2. Label elements

Hazard pictograms (GHS AU)

GHS07 GHS08

Signal word (GHS AU)	Danger
Hazard statements (GHS AU)	H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H350 - May cause cancer.
Precautionary statements (GHS AU)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352 - IF ON SKIN: Wash with plenty of water/…
P337+P313 - If eye irritation persists: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards not contributing to the classification

No additional information available

Additional information

2-Component-foilpack, contains:
Component A: Urethane methacrylate resin, inorganic filler
Component B: Dibenzoyl peroxide, phlegmatized



Name	General description	Quantity	Unit	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
HIT-HY 170, A		1	pcs (pieces)	Eye Irrit. 2A, H319 Skin Sens. 1, H317 Carc. 1B, H350
HIT-HY 170, B		1	pcs (pieces)	Skin Sens. 1, H317

SECTION 4: General advice

General advice	For professional users only

SECTION 5: Safe handling advice

General measures	Spilled material may present a slipping hazard
Environmental precautions	Prevent entry to sewers and public waters Notify authorities if liquid enters sewers or public waters
Storage conditions	Keep cool. Protect from sunlight.
Precautions for safe handling	Wear personal protective equipment Avoid contact with skin and eyes Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work Provide good ventilation in process area to prevent formation of vapour
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation Mechanically recover the product Store away from other materials.
For containment	Collect spillage.
Incompatible materials	Sources of ignition Direct sunlight
Incompatible products	Strong bases Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact	Rinse immediately with plenty of water Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists
First-aid measures after ingestion	Rinse mouth Get medical advice/attention. Do not induce vomiting Obtain emergency medical attention

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air Allow the victim to rest
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/… If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects after eye contact	May cause severe irritation
Symptoms/effects after skin contact	May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-HY 170, B

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date:23/03/2020 Revision date:23/03/2020 Supersedes: 19/11/2018 Version: 1.3

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 170, B
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

For professional use only

1.4. Supplier's details

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
2138 Rhodes NSW - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

1.5. Emergency phone number

Emergency number	+61 2 8748 1000

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Skin sensitisation, Category 1	H317

2.2. Label elements

Hazard pictograms (GHS AU)

GHS07

Signal word (GHS AU)	Warning
Contains	dibenzoyl peroxide (5 - 10 %)
Hazard statements (GHS AU)	H317 - May cause an allergic skin reaction.
Precautionary statements (GHS AU)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P302+P352 - IF ON SKIN: Wash with plenty of water/… P337+P313 - If eye irritation persists: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
dibenzoyl peroxide	94-36-0	5 - 10	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/…. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Symptoms caused by exposure

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 - 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

HIT-HY 170, B		
Australia	Local name	Benzoyl peroxide (Dibenzoyl peroxide)
Australia	TWA (mg/m³)	5 mg/m³
Australia	Remark (AU)	Sen - Respiratory and/or Skin Sensitiser.
Australia	Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

Exposure limit values for the other components

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls	Ensure good ventilation of the work station.

8.4. Personal protective equipment

Personal protective equipment	Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.
Hand protection	Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	EN 374

Eye protection: Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection: Wear suitable protective clothing

Environmental exposure controls	Avoid release to the environment.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.
Other information	Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	white
Odour	characteristic
Odour threshold	Not determined
pH	≈ 6
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	Not self-igniting
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative density	No data available
Density	1.7 g/cm³ DIN 51757
Solubility	Water: Not miscible
Log Pow	No data available
Viscosity	Viscosity, dynamic : 90 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available
Minimum ignition energy	No data available
SADT	65 °C
Fat solubility	No data available

SECTION 10: Stability and reactivity

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
Skin corrosion/irritation	Not classified pH: ≈ 6
Serious eye damage/irritation	Not classified pH: ≈ 6
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 170, B	
Viscosity, kinematic	52941.176 mm²/s
Density	1.7 g/cm³ DIN 51757
Viscosity, dynamic	90 Pa·s HN-0333

Potential adverse human health effects and symptoms	No additional information available

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Other information	Avoid release to the environment.

dibenzoyl peroxide (94-36-0)	
LC50 fish 2	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 Daphnia 1	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)

dibenzoyl peroxide (94-36-0)	
NOEC chronic fish	< 0.001
Log Pow	3.71
Log Koc	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)

12.2. Persistence and degradability

HIT-HY 170, B	
Persistence and degradability	Not established.

dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-HY 170, B	
Bioaccumulative potential	Not established.

dibenzoyl peroxide (94-36-0)	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

Ozone: Not classified

Other adverse effects: No additional information available

HIT-HY 170, B	
Fluorinated greenhouse gases	False

dibenzoyl peroxide (94-36-0)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste): Disposal must be done according to official regulations.

Product/Packaging disposal recommendations: After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials: Avoid release to the environment.

SECTION 14: Transport information

ADR	IMDG	IATA	RID
14.1. UN number			
Not regulated	Not regulated	Not regulated	Not regulated

ADR	IMDG	IATA	RID
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
Environmentally hazardous substances derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg)			
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

Specific storage requirement	No data available
Shock sensitivity	No data available

14.7. Additional information

Other information	not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7

Transport by road and rail

Not applicable

Transport by sea

Not applicable

Air transport

Special provisions (IATA)	A197

14.8. Hazchem or Emergency Action Code

Hazchem Code	Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Abbreviations and acronyms	ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road ATE - Acute Toxicity Estimate BCF - Bioconcentration factor DMEL - Derived Minimal Effect level CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 DNEL - Derived-No Effect Level EC50 - Median effective concentration IARC - International Agency for Research on Cancer IATA - International Air Transport Association IMDG - International Maritime Dangerous Goods LC50 - Median lethal concentration LD50 - Median lethal dose LOAEL - Lowest Observed Adverse Effect Level NOAEC - No-Observed Adverse Effect Concentration NOAEL - No-Observed Adverse Effect Level SDS - Safety Data Sheet vPvB - Very Persistent and Very Bioaccumulative RID - Regulations concerning the International Carriage of Dangerous Goods by Rail REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 PNEC - Predicted No-Effect Concentration PBT - Persistent Bioaccumulative Toxic
Revision date	23/03/2020
Other information	None.

Classification:

Skin Sens. 1	H317

Full text of H-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Org. Perox. B	Organic Peroxides, Type B
Skin Sens. 1	Skin sensitisation, Category 1
H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SDS_AU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-HY 170, A

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date:12/02/2020 Revision date:12/02/2020 Supersedes: 16/11/2018 Version: 2.0

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form	Mixture
Product name	HIT-HY 170, A
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

For professional use only

1.4. Supplier's details

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
2138 Rhodes NSW - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

1.5. Emergency phone number

Emergency number	+61 2 8748 1000

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1B	H350

2.2. Label elements

Hazard pictograms (GHS AU)

GHS07 GHS08

Signal word (GHS AU)	Danger
Contains	2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (10 - 25 %); 2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (1 - 2.5 %); 1,2-dihydroxybenzene (0.1 - 1 %)
Hazard statements (GHS AU)	H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H350 - May cause cancer.
Precautionary statements (GHS AU)	P280 - Wear eye protection, protective clothing, protective gloves. P262 - Do not get in eyes, on skin, or on clothing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P302+P352 - IF ON SKIN: Wash with plenty of water/… P337+P313 - If eye irritation persists: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	27813-02-1	10 - 25	Eye Irrit. 2A, H319 Skin Sens. 1, H317
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	2082-81-7	1 - 2.5	Skin Sens. 1B, H317
1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3	0.1 - 1	Acute Tox. 2 (Oral), H300 Eye Irrit. 2A, H319 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
1,2-dihydroxybenzene	120-80-9	0.1 - 1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 2, H341 Carc. 1B, H350

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general: Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact: Wash contaminated clothing before reuse. Wash with plenty of water/…. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion: Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Symptoms caused by exposure

Symptoms/effects after skin contact: May cause an allergic skin reaction.

Symptoms/effects after eye contact: May cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Water spray. Carbon dioxide. Dry powder. Foam. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire: Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures: Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 - 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

HIT-HY 170, A		
Australia	Local name	Quartz [Silica – Crystalline]
Australia	TWA (mg/m³)	0.05 mg/m³ respirable dust

HIT-HY 170, A		
Australia	Remark (AU)	Carcinogenicity Category 1A – Known to have carcinogenic potential for humans. The classification of a chemical into this category is based largely on human evidence from studies that have established a causal relationship between human exposure and the development of cancer.
Australia	Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

1,2-dihydroxybenzene (120-80-9)		
Australia	Local name	Catechol
Australia	TWA (mg/m³)	23 mg/m³
Australia	TWA (ppm)	5 ppm

Exposure limit values for the other components

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls: Ensure good ventilation of the work station.

8.4. Personal protective equipment

Personal protective equipment: Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.

Hand protection: Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12	EN 374

Eye protection: Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection: Wear suitable protective clothing

Environmental exposure controls: Avoid release to the environment.

Consumer exposure controls: Avoid contact during pregnancy/while nursing.

Other information: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state: Solid

Appearance: Thixotropic paste.

Colour: Light grey

Odour	characteristic
Odour threshold	Not determined
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	> 109 °C DIN EN ISO 1523
Auto-ignition temperature	Not self-igniting
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative density	No data available
Density	1.65 g/ml AW 4.3.23
Solubility	Water: Not miscible
Log Pow	No data available
Viscosity	Viscosity, dynamic : 100 Pa·s HN-0333
Explosive properties	Product is not explosive.
Explosive limits	No data available
Minimum ignition energy	No data available
Fat solubility	No data available

SECTION 10: Stability and reactivity

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	>= 5000 mg/kg bodyweight (Rabbit; Experimental value)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LD50 oral rat	25 mg/kg
LD50 dermal rat	> 2000 mg/kg

1,2-dihydroxybenzene (120-80-9)	
LD50 oral rat	300 mg/kg
LD50 dermal rat	600 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	>= 2.8 mg/l/4h

Skin corrosion/irritation	Not classified

Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	May cause cancer.
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-HY 170, A	
Viscosity, kinematic	60606.061 mm²/s
Density	1.65 g/ml AW 4.3.23
Viscosity, dynamic	100 Pa·s HN-0333

Potential adverse human health effects and symptoms	No additional information available

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Other information	Avoid release to the environment.

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 fish 1	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 Daphnia 1	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 (algae)	> 97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	<= 100
BCF fish 2	3.2 Quantitative structure-activity relationship (QSAR)
Log Pow	0.97 (OECD 102 method)
Log Koc	1.9 (log Koc, Calculated value)
Threshold limit algae 1	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit algae 2	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 other aquatic organisms 1	9.79 mg/l
NOEC (acute)	7.51 mg/l
NOEC (chronic)	20 mg/l
Log Pow	3.1

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LC50 fish 1	≈ 17 mg/l
LC50 other aquatic organisms 1	245 mg/l
EC50 Daphnia 1	28.8 mg/l
NOEC (acute)	57.8 mg/l
BCF fish 1	≈
Log Kow	2.1

1,2-dihydroxybenzene (120-80-9)	
LC50 fish 1	9.22 mg/l
LC50 other aquatic organisms 1	22 mg/l

12.2. Persistence and degradability

HIT-HY 170, A	
Persistence and degradability	Not established.

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Not rapidly degradable	
Biodegradation	84 %

12.3. Bioaccumulative potential

HIT-HY 170, A	
Bioaccumulative potential	Not established.

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
BCF fish 1	See section 12.1 on ecotoxicology
BCF fish 2	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Log Pow	See section 12.1 on ecotoxicology

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Kow	See section 12.1 on ecotoxicology

12.4. Mobility in soil

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil.

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Log Pow	See section 12.1 on ecotoxicology

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Log Kow	See section 12.1 on ecotoxicology

12.5. Other adverse effects

Ozone: Not classified

Other adverse effects: No additional information available

HIT-HY 170, A	
Fluorinated greenhouse gases	False

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Fluorinated greenhouse gases	False

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Fluorinated greenhouse gases	False

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Fluorinated greenhouse gases	False

1,2-dihydroxybenzene (120-80-9)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

ADR	IMDG	IATA	RID
14.1. UN number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

Specific storage requirement	No data available
Shock sensitivity	No data available

14.7. Additional information

Other information	No supplementary information available

Transport by road and rail

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

14.8. Hazchem or Emergency Action Code

Hazchem Code	Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE - Acute Toxicity Estimate

BCF - Bioconcentration factor

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DMEL - Derived Minimal Effect level

DNEL - Derived-No Effect Level

vPvB - Very Persistent and Very Bioaccumulative

SDS - Safety Data Sheet

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

PNEC - Predicted No-Effect Concentration

PBT - Persistent Bioaccumulative Toxic

OECD - Organisation for Economic Co-operation and Development

NOEC - No-Observed Effect Concentration

NOAEL - No-Observed Adverse Effect Level

NOAEC - No-Observed Adverse Effect Concentration

LOAEL - Lowest Observed Adverse Effect Level

LD50 - Median lethal dose

LC50 - Median lethal concentration

IMDG - International Maritime Dangerous Goods

IATA - International Air Transport Association

EC50 - Median effective concentration

IARC - International Agency for Research on Cancer

Revision date: 12/02/2020

Other information: None.

Classification:

Eye Irrit. 2A	H319
Skin Sens. 1	H317
Carc. 1B	H350

Full text of H-statements:

Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 3	Hazardous to the aquatic environment — Acute Hazard, Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Muta. 2	Germ cell mutagenicity, Category 2

Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.

SDS_AU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.