

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Issue date: 21/02/2025

Revision date: 21/02/2025

Supersedes: 22/11/2021

Version: 2.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form	Mixture
Trade name	CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750
Product code	BU Fire Protection Foam

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Details of manufacturer or importer

Supplier

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
Rhodes NSW 2138
Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

Department issuing data specification sheet:

Hilti AG
Feldkircherstraße 100
Schaan 9494
Liechtenstein
T +423 234 2111
product.compliance-fire.protection@hilti.com

1.5. Emergency phone number

Emergency number	Emergency CONTACT (24-Hour-Number): GBK GmbH Global Regulatory Compliance +49 (0)6132-84463
------------------	--

Country	Organisation/Company	Address	Emergency number	Comment
Australia	NSW Poisons Information Centre The Children's Hospital at Westmead	Locked Bag 4001 NSW 2145	13 11 26	

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)



Flame

Exclamation mark

Health hazard

Signal word (GHS AU)

Danger

Contains

4,4'-diphenylmethanediisocyanate, isomeres and homologues (10 – 25 %); Reaction products of phosphoryl trichloride and 2-methyloxirane (10 – 25 %)

Hazard statements (GHS AU)

H222 - Extremely flammable aerosol
 H229 - Pressurised container: May burst if heated
 H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
 H335 - May cause respiratory irritation
 H351 - Suspected of causing cancer
 H373 - May cause damage to organs through prolonged or repeated exposure
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source.
 P251 - Do not pierce or burn, even after use.
 P260 - Do not breathe spray.
 P280 - Wear eye protection, protective clothing, protective gloves.
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements (GHS AU)

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
4,4'-diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	10 – 25	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Reaction products of phosphoryl trichloride and 2-methyloxirane	13674-84-5	10 – 25	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Chronic 3, H412
Dimethyl ether (Propellant gas (Aerosol))	115-10-6	5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
isobutane (Propellant gas (Aerosol))	75-28-5	5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
propane (Propellant gas (Aerosol))	74-98-6	2.5 – 5	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	Toxic fumes may be released. Vapours may form explosive mixture with air.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.
----------------------	---------------------------------

6.1.2. For emergency responders

Protective equipment	Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up	Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. May form flammable/explosive vapour-air mixture. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures

Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Storage temperature

5 – 25 °C

Heat and ignition sources

Keep away from heat and direct sunlight. Keep away from ignition sources.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Dimethyl ether (115-10-6)	
Australia - Occupational Exposure Limits	
Local name	Dimethyl ether
OES TWA	760 mg/m ³
	400 ppm
OES STEL	950 mg/m ³
	500 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls

Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment

Protective clothing. Safety glasses. Gloves. Avoid all unnecessary exposure.

Hand protection

Wear suitable gloves tested to EN374. Suitable for short-term work or as a splash guard: Nitrile rubber gloves (> 0.1 mm). In case of permanent product contact:

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0,35mm		
Disposable gloves	Butyl rubber	6 (> 480 minutes)	>0,35mm		

Eye protection

Chemical goggles or safety glasses

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Skin and body protection

Respiratory protection

Wear suitable protective clothing

Not necessary with sufficient ventilation. Ensure good ventilation of the work station. Open windows during application to ensure natural ventilation. If the occupational exposure limit is exceeded: Wear appropriate mask. (e.g. gas filter type A1-P2 according to EN 14387)

Personal protective equipment symbol(s)



Environmental exposure controls

Other information

Avoid release to the environment.

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state	Liquid
Appearance	Aerosol.
Colour	Manila
Odour	ether-like odour
Odour threshold	No data available
pH	No data available
pH solution	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Flammability	No data available
Vapour pressure	Vapour pressure: 5100 hPa
Relative density	No data available
Density	Density: 1.049 g/cm ³
Solubility	No data available
Partition coefficient n-octanol/water (Log Pow)	No data available
Explosive properties	Pressurised container: May burst if heated.
Explosive limits	No data available
Minimum ignition energy	No data available
Fat solubility	No data available

SECTION 10: Stability and reactivity

Reactivity	Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	Not established.
Possibility of hazardous reactions	Not established.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)

LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)
---------------	---

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
LD50 dermal	9400 mg/kg
LC50 Inhalation - Rat	0.49 mg/l
propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
isobutane (75-28-5)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Suspected of causing cancer.
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified
CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750	
Vaporizer	Aerosol

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h, Literature study)
BCF - Fish [1]	268.1 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4100 mg/l (NEN 6504: Water - Determination of toxicity with Poecilia reticulata, 96 h, Poecilia reticulata, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 4400 mg/l (NEN 6501: Water - Determination of toxicity with Daphnia magna, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)
Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)
isobutane (75-28-5)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
12.2. Persistence and degradability	
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
propane (74-98-6)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.
Dimethyl ether (115-10-6)	
Persistence and degradability	Non degradable in the soil. Not readily biodegradable in water.
isobutane (75-28-5)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
BCF - Fish [1]	268.1 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
isobutane (75-28-5)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

12.4. Mobility in soil

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Surface tension	No data available in the literature
Ecology - soil	Adsorbs into the soil.
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
propane (74-98-6)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)
Dimethyl ether (115-10-6)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).
Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)
isobutane (75-28-5)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)

12.5. Other adverse effects

Ozone : Not classified
 Other adverse effects : No additional information available

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750	
Fluorinated greenhouse gases	False
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Fluorinated greenhouse gases	False
propane (74-98-6)	
Fluorinated greenhouse gases	False
Dimethyl ether (115-10-6)	
Fluorinated greenhouse gases	False
isobutane (75-28-5)	
Fluorinated greenhouse gases	False
Reaction products of phosphoryl trichloride and 2-methyloxirane (13674-84-5)	
Fluorinated greenhouse gases	False

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 13: Disposal considerations

<p>Waste treatment methods</p> <p>Product/Packaging disposal recommendations</p> <p>Ecological information</p>	<p>Dispose of contents/container in accordance with licensed collector's sorting instructions.</p> <p>Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</p> <p>Avoid release to the environment.</p>
--	--

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	5F
Special provisions (ADR)	190, 327, 344, 625
Limited quantities (ADR)	1I
Packing instructions (ADR)	P207, LP02
Mixed packing provisions (ADR)	MP9
Transport category (ADR)	2
Tunnel restriction code (ADR)	D

Transport by sea

Special provisions (IMDG)	63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	SP277
Packing instructions (IMDG)	P207, LP02
EmS-No. (Fire)	F-D

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

EmS-No. (Spillage)	S-U
Stowage category (IMDG)	None
MFAG-No	126
Air transport	
PCA packing instructions (IATA)	203
PCA max net quantity (IATA)	75kg
CAO packing instructions (IATA)	203
Special provisions (IATA)	A145, A167, A802
Inland waterway transport	
Classification code (ADN)	5F
Special provisions (ADN)	19, 327, 344, 625
Limited quantities (ADN)	1 L
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP, EX, A
Ventilation (ADN)	VE01, VE04
Number of blue cones/lights (ADN)	1
Rail transport	
Special provisions (RID)	190, 327, 344, 625
Limited quantities (RID)	1L
Packing instructions (RID)	P207, LP02

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status All the chemicals contained in this product are listed introductions

15.2. International agreements

No additional information available

SECTION 16: Other information

Indication of changes:

Composition/information on ingredients.

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Abbreviations and acronyms

CAS-No. - Chemical Abstract Service number
 ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE - Acute Toxicity Estimate
 BCF - Bioconcentration factor
 BLV - Biological limit value
 BOD - Biochemical oxygen demand (BOD)
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 DMEL - Derived Minimal Effect level
 DNEL - Derived-No Effect Level
 EC-No. - European Community number
 EC50 - Median effective concentration
 ED - Endocrine disrupting properties
 EN - European Standard
 IARC - International Agency for Research on Cancer
 IATA - International Air Transport Association
 IMDG - International Maritime Dangerous Goods
 IOELV - Indicative Occupational Exposure Limit Value
 LC50 - Median lethal concentration
 LD50 - Median lethal dose
 LOAEL - Lowest Observed Adverse Effect Level
 N.O.S. - Not Otherwise Specified
 NOAEC - No-Observed Adverse Effect Concentration
 NOAEL - No-Observed Adverse Effect Level
 NOEC - No-Observed Effect Concentration
 vPvB - Very Persistent and Very Bioaccumulative
 WGK - Water Hazard Class
 VOC - Volatile Organic Compounds
 SDS - Safety Data Sheet
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 PNEC - Predicted No-Effect Concentration
 PBT - Persistent Bioaccumulative Toxic
 OEL - Occupational Exposure Limit
 OECD - Organisation for Economic Co-operation and Development
 COD - Chemical oxygen demand (COD)
 ThOD - Theoretical oxygen demand (ThOD)
 TRGS - Technical Rules for Hazardous Substances
 TLM - Median Tolerance Limit
 STP - Sewage treatment plant
 21/02/2025

Revision date

Classification	
Aerosol 1	H222;H229
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Classification	
STOT SE 3	H335
STOT RE 2	H373

Full text of H-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Gas 1	Flammable gases, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

SDS_AU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.